QUICK REFERENCE GUIDE > GDSBE1-302-L Date: 04.07.2024 > 1

30" Griddle/Side Burner, LPG

Series 9

Stainless Steel | LPG



Get the best of both worlds with a Griddle and Dual Side Burner. Combining the quick cooking griddle with two side burners for sautéing and simmering, this is a hard working product for the outdoor kitchen where space is limited.

- Seamless installation and interconnectivity between products allows for unified operation, from ignition to dial illumination
- · Fast, weather resistant ignition system
- Made from durable, hardwearing 304 stainless steel

 Able to be built-in or mounted on a freestanding cart (Grill Cart sold separately - CAD1-30E)

DIMENSIONS

Height	10 1/2 "
Width	30 "
Depth	26 7/8 "

FEATURES & BENEFITS

Cook It Your Way

Cook it your way with a variety of flexible cooking methods provided by DCS cooking attachments.

Designed To Match

With a matching look across all DCS Series 9 products, you can create a stylish, cohesive design for your Outdoor kitchen. Seamless installation and interconnectivity between products* allows for unified operation, from ignition to dial illumination.

Convenient And Reliable

Illuminated dials immediately and intuitively tell you at a glance if the product is on. Get grilling quickly with a fast, weather resistant ignition system that works every time.

Durable And Hard Wearing

Made from durable, hardwearing 304 stainless steel with stainless steel weather covers to ensure they are protected from the elements.

SPECIFICATIONS

Accessories (sold separately)

Optional cart mount CAD1-30E

Burners

Number of side burners	2
Number of U-burners	1

Cooking Surface Area

Total cooking area	244 sq.in.
--------------------	------------

Features

Griddle plate	•	
Ignition system	Surface	
Side burners		
Stainless steel cover included	•	

Finish

Available in built-in or on cart applications	•
Material	304 grade stainless steel
Weather resistant	•

Gas Requirements

1/2" NPT male with 3/8" in flare adapter	•
Gas type	LPG
LP hose with regulator and Type 1 connector	•
Operational pressure	11" W.C.
Supply pressure	12" to 14" W.C.



QUICK REFERENCE GUIDE > GDSBE1-302-L Date: 04.07.2024 > 2

Installation Dimensions

Cutout depth (proud) 22 3/4 "

Cutout height (proud) 10 1/8 "

Cutout width (proud) 28 1/2 "

Performance

Side burner power 17000 BTU

Total Power 46000 BTU

U-burner power 12000 BTU

Power Requirements

Power and logic interconnectivity

Supply frequency

60Hz

Supply voltage

120 V

Warranty

Parts and labor 2 years

SKU 71470

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

Other product downloads available at dcsappliances.com

Planning Guide - Professional Grills Series 9 Outdoor Kitchen

↓ Revit-18 Griddle Side Burner

Rhino-5 Griddle Side Burner

Rhino-5 Griddle Side Burner with Insulated Jacket

Service and Warranty

SketchUp-8 Griddle Side Burner

SketchUp-8 Griddle Side Burner with Insulated Jacket

Installation Guide EN

↓ User Guide EN

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com

