

## 30" Grill, LPG

Series 7

Stainless Steel | LPG



Designed with flexibility in mind, DCS Grills allow you to cook a wide variety of meals and are engineered to deliver the functionality and power demanded by a professional chef. DCS Grills are hand-finished to perfection to complement the quality of the DCS premium outdoor kitchen and built to withstand the demands of the serious cook and the extremes of mother nature. Available in Natural and LP Gas.

### DIMENSIONS

Height 24 1/4 "

Width 30 "  
Depth 26 5/8 "

### FEATURES & BENEFITS

#### Stainless Steel Burners

The precision ported U-shaped stainless steel burners are rated at a massive 25,000BTU each, offering premium quality and performance. A heat shield directs heat upwards maximizing heating efficiency.

#### Ceramic Radiant Technology

A layer of ceramic rods provides intense yet even heat. It gives a consistent grilling surface, with controlled heat rather than direct fire.

#### Direct Burner Ignition

An ergonomic ignition solution, where burners are lit directly from the corresponding knobs.

#### Smart Beam™ Grill Light

A halogen light is designed to illuminate the entire cooking surface for perfect night grilling.

#### Temperature Gauge - Zero To Sear

Go from zero to sear with DCS Grills' new built-in temperature gauge. It lets you know exactly how hot the grill is, even when the hood is down.

#### Rotisserie Made Easy

Inspired by our commercial heritage, DCS Rotisserie Grills are the perfect package of robust construction, powerful motor, consistent temperatures and strong forks. DCS Rotisserie Grill models feature a dedicated infrared rotisserie burner, providing controlled searing up to 14,000 BTU per hour. The heavy-duty motor allows you to load your Thanksgiving turkey (and more!), while the Smart Beam™ Grill Light illuminates the entire cooking surface for perfect night grilling. Load up your new DCS Grill's rotisserie then sit back and let the grill do the work.

### SPECIFICATIONS

#### Accessories (sold separately)

Built-in grill cover	ACBI-30
Insulated jacket	BGB30-IJS (optional)
On cart grill cover	ACC-30
Optional cart mount	CAD1-30 / BGB30-CSS

#### Burners

Number of U-burners 2

#### Cooking Surface Area

Primary cooking area 553 sq.in.  
Total cooking area 748 sq.in.  
Warming rack area 195 sq.in.

#### Features

Full surface searing	•
Hood temperature gauge	•
Ignition system	<b>Spark</b>
Metal dials	•
Rotisserie	•
Warming rack	•

Total Power	<b>64000 BTU</b>
U-burner power	<b>25000 BTU</b>

- ↓ Sketchup-8 Grill
- ↓ Sketchup-8 Grill with Insulated Jacket
- ↓ Installation & User Guide EN / Guide d'installation et guide d'utilisation FR

**Power Requirements**

Grill power supply	<b>9V Battery for Ignition</b>
Rotisserie power supply	<b>120V 60Hz</b>

**A PEACE OF MIND SALE**

**24 Hours 7 Days a Week Customer Support**

T 1.888.936.7872 W [www.dcsappliances.com](http://www.dcsappliances.com)

**Finish**

Material	<b>304 grade stainless steel</b>
Weather resistant	•

SKU 71451

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

[Other product downloads available at dcsappliances.com](http://www.dcsappliances.com)

- ↓ 2D-DWG Grill
- ↓ 2D-DWG Grill with Insulated Jacket
- ↓ 2D-DXF Grill with Insulated Jacket
- ↓ Datasheet Grill
- ↓ Datasheet Grill with Insulated Jacket
- ↓ Revit-18 Grill
- ↓ Rhino-5 Grill
- ↓ Rhino-5 Grill
- ↓ Rhino-5 Grill
- ↓ Rhino-5 Grill with Insulated Jacket
- ↓ Rhino-5 Grill with Insulated Jacket
- ↓ Service and Warranty

**Gas Requirements**

1/2" NPT male with 3/8" in flare adapter	•
Gas type	<b>LPG</b>
LP hose with regulator and Type 1 connector	•
Operational pressure	<b>11" W.C.</b>
Supply pressure	<b>12" to 14" W.C.</b>

**Installation Dimensions**

Cutout depth (proud)	<b>22 3/4 "</b>
Cutout height (proud)	<b>10 1/8 "</b>
Cutout width (proud)	<b>28 1/2 "</b>
Insulated jacket for proud cut-out	<b>Varies - check manual</b>

**Performance**

Rotisserie burner power	<b>14000 BTU</b>
-------------------------	------------------