QUICK REFERENCE GUIDE > GDE1-30-N

30" Series 9 Griddle, Natural Gas

Series 9

Stainless Steel | Natural Gas



Expand your outdoor kitchen options with quick cooking on the griddle. Designed with flexibility in mind, this 30" griddle can either be built-in or mounted on a freestanding cart (Grill Cart sold separately - CAD1-30E).

- Large griddle surface with precise temperature control
- Separate temperature zones and even heat distribution
- Interconnected illuminated dials to match the suite of DCS Series 9 products
- · Removable slide out drip tray

DIMENSIONS

 Height
 10 1/2 "

 Width
 30 "

 Depth
 26 7/8 "

FEATURES & BENEFITS

Quick, Precision Cooking

Bring more cooking options to your outdoor kitchen with quick cooking on the griddle. Cook different foods at the same time with precision thermostatic control, separate temperature zones and even heat distribution.

Designed To Match

With a matching look across all DCS Series 9 products, you can create a stylish, cohesive design for your Outdoor kitchen. Seamless installation and interconnectivity between products* allows for unified operation, from ignition to dial illumination.

Safe And Convenient

Clean up is simple due to the removable slide out drip tray. For your safety, a flame failure device cuts the gas if a burner goes out.

Heavy Duty Build

Designed to withstand high temperatures and all types of weather conditions, the griddle plate is made from durable, 8mm thick 304 stainless steel.

SPECIFICATIONS

Accessories (sold separately)

Optional cart mount CAD1-3E

Burners

Number of U-burners

Cooking Surface Area

Total cooking area 500 sq.in.

Features

Dual temperature zones

Griddle plate

Ignition system

Surface

Stainless steel cover included

Finish

Available in built-in or on cart applications

Material

304 grade
stainless steel

Weather resistant

Gas Requirements

1/2" NPT male with 3/8" in flare adapter

Gas type

NG

Operational pressure

4" W.C.

Supply pressure

6" to 9" W.C.

Installation Dimensions

Cutout depth (proud) 22 3/4 "



QUICK REFERENCE GUIDE > GDE1-30-N

Cutout height (proud)	10 1/8 "
Cutout width (proud)	28 1/2 "
Performance	
Total Power	40000 BTU
U-burner power	20000 BTU
Power Requirements	
Power and logic interconnectivity	•
Supply frequency	60Hz
Supply voltage	120 V
Warranty	
	2 years

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

Other product downloads available at dcsappliances.com

 $\underline{\downarrow}$

SKU

2D-DWG Griddle

- ↓ 2D-DXF Griddle
- ↓ Data Sheet Griddle
- Planning Guide EN Professional Grills Series 9 Outdoor Kitchen
- → Planning Guide FR Professional Grills Series 9 Outdoor
 Kitchen
- → Planning Guide SP Professional Grills Series 9 Outdoor
 Kitchen
- ↓ Revit-18 Griddle
- Rhino-5 Griddle with Lid
- ↓ Rhino-5 Griddle without Lid
- ↓ Rhino-5 Griddle with Insulated Jacket
- ↓ Service and Warranty
- ↓ SketchUp-8 Griddle with Lid
- SketchUp-8 Griddle without Lid
- ↓ SketchUp-8 Griddle
- User Guide FR

A PEACE OF MIND SALE

71464

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com

