QUICK REFERENCE GUIDE > BE1-48RCI-L Date: 17.07.2024 > 1

48" Grill with Infrared Sear Burner, LPG

Series 9

Stainless Steel | LPG




Taking your grilling experience to the next level, this Series 9 builtin 48" grill provides the ultimate grilling space for premium outdoor kitchens.

- Infrared sear burner for incredibly fast searing up to 24,000 BTU/hr
- · Cater for a crowd with the secondary cooking surface
- Build into an outdoor BBQ island, or add a cart for a freestanding grill
- U-burners deliver 25,000 BTU/hr total power per burner with precise heat control from 300°F to 1100°F

DIMENSIONS

Height 27 1/4 "
Width 47 15/16 "
Depth 26 7/8 "



FEATURES & BENEFITS

The Perfect Sear

A dedicated searing zone with a dynamic infrared burner allows you to experience a new level of versatility, using a range of cooking methods. The improved dual rail design offers increased control and faster heating, so you can achieve the perfect sear every time.

Charcoal Smoker Tray

Enjoy a smoky barbecue flavour with the ease of instant gas flame ignition. Grill directly on the cooking grate or add wood chips for extra smoke. A W-shaped tray with adjustable vents helps the charcoal last longer.

Heavy-Duty Infrared Rotisserie

An infrared rotisserie burner provides controlled searing heat up to 18,000BTU. Perfect for entertaining, the heavy-duty motor can easily turn a 50lb load. The rotisserie rod is conveniently stored under the drip pan handle.

Intuitive Lighting

Brilliant 12-volt lighting safely illuminates the entire grilling surface when you open the lid. Ideal for night-time cooking, the bezel dial lighting glows white when the grill is on, and orange when the gas and grill are in use.

Easy Lifting Hood

The hood can be opened using one hand for better access and visibility when cooking. You can easily accommodate larger food loads with extra space under the hood.

Extra Cooking Area

Effortlessly cook for a crowd with a secondary cooking space. You can fit a grill pan for slow cooking, roasting and making sauces, or to keep food warm after searing.

Grease Management System™

Our Grease Management System™ reduces flare-ups by channelling grease and oils away from the burner flames during grilling.

SPECIFICATIONS

Accessories (sold separately)

6" accessory storage

ASE6-48

Built-in grill cover

ACBI-48E



QUICK REFERENCE GUIDE > BE1-48RCI-L Date: 17.07.2024 > 2

Griddle plate	BGC-GP	Finish		Supply frequency 60	Hz
Insulated jacket	BGA48-IJS (optional)	Material	304 grade stainless steel	Supply voltage 120	0 V
Insulated jacket (with storage accessory unit)	BGA54-IJS (optional)	Weather resistant	•		
On cart grill cover	ACC-48E			SKU 71	1592
Optional cart mount	CAD-48E	Gas Requirements			
		1/2" NPT male	•	The product dimensions and specifications in this page apply to the specif	iic
Burners		Gas type	LPG	product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefo	ore
Number of U-burners	3	LP hose with regulator and Type 1 connector	•	check with Fisher & Paykel's Customer Care Centre to ensure this page	10
Sear burner zone	•	Operational pressure	11" W.C.	correctly describes the model currently available. © DCS by Fisher & Payke Appliances Limited 2020	əl
		Supply pressure	12" to 14" W.C.	Appliances Limited 2020	
Cooking Surface Area				Other product downloads available at dcsappliances.com	
Primary cooking area	855 sq.in.	Installation Dimensions			
Secondary cooking area	738 sq.in.	Cutout depth (proud)	22 3/4 "		
Total cooking area	1593 sq.in.	Cutout height (proud)	10 1/8 "	2D-DWG Grill with Storage Unit	
		Cutout width (proud)	45 3/4 "	2D-DWG Grill with Storage Unit and Insulated Jacket	
		Insulated jacket for proud cut-out	Varies - check		
Features			manual		
Double sided grilling grates	flat and angled				
Double stated grilling grates	position	Performance			
Full charcoal burner/smoker	•			Data Sheet Grill Insulated Jacket	
Full surface searing	•	Rotisserie burner power	18000 BTU	 Data Sheet Grill with ASE648 Storage Unit 	
Grease management system™	•	Sear burner power	24000 BTU	Data Sheet Grill with BGA48-IJS Insulated Jacket	
Hood temperature gauge	•	Total Power	117000 BTU	⊥ Installation Guide Grill EN	
Ignition system	Hot surface	U-burner power	25000 BTU	$ ule{ }$ Installation Guide Grill on Cart EN	
Metal dials	•	Weight rotisserie can handle	50 lbs	✓ Guide d'installation FR	
Rotisserie	•			→ Guía de instalación SP	
Secondary cooking	2-level racks and tray	Power Requirements		✓ Planning Guide - Professional Grills Series 9 Outdoor Kitch✓ Revit-18 Grill	ien
Wireless temperature sensor compatible	•	Rotisserie power supply	120V 60Hz	Revit-18 Grill with Storage Unit	



QUICK REFERENCE GUIDE > BE1-48RCI-L Date: 17.07.2024 > 3

- ↓ Rhino-5 Grill
- ↓ Rhino-5 Grill with Storage Unit
- Rhino-5 Grill with Storage Unit and Insulated Jacket
- Service and Warranty
- ↓ Sketchup-8 Grill
- ↓ Sketchup-8 Grill with Storage Unit and Insulated Jacket
- ↓ Sketchup-8 Grill with Storage Unit and Insulated Jacket
- ↓ User Guide Grill EN
- ↓ Guide d'utilisation FR
- ↓ Guía del usuario SP

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com