QUICK REFERENCE GUIDE > BE1-36RCI-N

36" Grill with Infrared Sear Burner, Natural Gas

Series 9

Stainless Steel | Natural Gas



This Series 9 built-in 36" grill is designed for premium outdoor kitchens and will take your outdoor cooking experience to the next level.


- Infrared sear burner for incredibly fast searing up to 24,000 BTU/hr
- · Cater for a crowd with the secondary cooking surface
- Build into an outdoor BBQ island, or add a cart for a freestanding grill
- U-burners deliver 25,000 BTU/hr total power per burner with precise heat control from 300°F to 1100°F

DIMENSIONS

 Height
 27 1/4 "

 Width
 35 15/16 "

 Depth
 26 7/8 "



FEATURES & BENEFITS

The Perfect Sear

A dedicated searing zone with a dynamic infrared burner allows you to experience a new level of versatility, using a range of cooking methods. The improved dual rail design offers increased control and faster heating, so you can achieve the perfect sear every time.

Charcoal Smoker Tray

Enjoy a smoky barbecue flavour with the ease of instant gas flame ignition. Grill directly on the cooking grate or add wood chips for extra smoke. A W-shaped tray with adjustable vents helps the charcoal last longer.

Heavy-Duty Infrared Rotisserie

An infrared rotisserie burner provides controlled searing heat up to 14,000BTU. Perfect for entertaining, the heavy-duty motor can easily turn a 50lb load. The rotisserie rod is conveniently stored under the drip pan handle.

Intuitive Lighting

Brilliant 12-volt lighting safely illuminates the entire grilling surface when you open the lid. Ideal for night-time cooking, the bezel dial lighting glows white when the grill is on, and orange when the gas and grill are in use.

Easy Lifting Hood

The hood can be opened using one hand for better access and visibility when cooking. You can easily accommodate larger food loads with extra space under the hood.

Extra Cooking Area

Effortlessly cook for a crowd with a secondary cooking space. You can fit a grill pan for slow cooking, roasting and making sauces, or to keep food warm after searing.

Grease Management System™

Our Grease Management System™ reduces flare-ups by channelling grease and oils away from the burner flames during grilling.

SPECIFICATIONS

Accessories (sold separately)

6" accessory storage

ASE6-36

Built-in grill cover

ACBI-36E



QUICK REFERENCE GUIDE > BE1-36RCI-N Date: 17.07.2024 > 2

Griddle plate	BGC-GP	Finish		Supply voltage 120 V	
Insulated jacket	BGA36-IJS (optional)	Material	304 grade stainless steel		
Insulated jacket (with storage accessory unit)	BGA42-IJS (optional)	Weather resistant	•	SKU 71593	
On cart grill cover	ACC-36E				
Optional cart mount	CAD-36E	Gas Requirements		The product dimensions and specifications in this page apply to the specific	
		1/2" NPT male	•	product and model. Under our policy of continuous improvement, these	
Burners		Gas type	NG	dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page	
Number of U-burners	2	Operational pressure	4" W.C.	correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020	
Sear burner zone	•	Supply pressure	6" to 9" W.C.		
Cooking Surface Area		Installation Dimensions		Other product downloads available at dcsappliances.com	
Primary cooking area	630 sq.in.	Cutout depth (proud)	22 3/4 "	<u>↓</u> 2D-DWG Grill	
Secondary cooking area	534 sq.in.	Cutout height (proud)	10 1/8 "		
Total cooking area	1164 sq.in.	Cutout width (proud)	34 1/2 "	2D-DWG Grill with Storage Unit and Insulated Jacket	
		Insulated jacket for proud cut-out	Varies - check		
			manual		
Features					
Double sided grilling grates	flat and angled	Performance			
	position	Daties wie bewegen aus en	14000 PTU	Data Sheet Grill with ASE636 Storage Unit Data Sheet Grill with ASE636 Storage Unit	
Full charcoal burner/smoker	•	Rotisserie burner power	14000 BTU	Data Sheet Grill with BGA36-IJS Insulated Jacket	
Full surface searing	•	Sear burner power	24000 BTU		
Grease management system™	•	Total Power	88000 BTU		
Hood temperature gauge	•	U-burner power	25000 BTU		
Ignition system	Hot surface	Weight rotisserie can handle	50 lbs	→ Guía de instalación SP	
Metal dials	•			Planning Guide - Professional Grills Series 9 Outdoor Kitchen	
Rotisserie	•			↓ Revit-18 Grill	
Secondary cooking	2-level racks and	Power Requirements		Revit-18 Grill with Storage Unit	
, <u> </u>	tray	Rotisserie power supply	120V 60Hz	★ Rhino-5 Grill The state of the s	
Wireless temperature sensor compatible	•	Supply frequency	60 Hz	↓ Rhino-5 Grill with Storage Unit	



QUICK REFERENCE GUIDE > BE1-36RCI-N Date: 17.07.2024 > 3

- Rhino-5 Grill with Storage Unit and Insulated Jacket
- ↓ Rhino-5 Grill with Insulated Jacket
- ↓ Service and Warranty
- ↓ Sketchup-8 Grill
- ↓ Sketchup-8 Grill with Storage Unit
- ↓ Sketchup-8 Grill with Storage Unit and Insulated Jacket
- ↓ Sketchup-8 Grill with Insulated Jacket
- ↓ User Guide Grill EN
- ↓ Guide d'utilisation FR
- ↓ Guía del usuario SP

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com