QUICK REFERENCE GUIDE > PBE1-24-L Date: 17.12.2024 > 1

24" Series 9 Power Burner, LPG

Series 9

Stainless Steel | LPG



Easily cook for a crowd on the impressive DCS Power Burner. Designed to support different sized pots and woks, it combines powerful heat with precise temperature control from 70,000 to 1,300 BTU.

- Grates are specially designed to provide stability for pots and woks of all sizes
- Combines powerful heat with precise temperature control from 70,000 to 1,300 BTU giving you flexibility for everything from a rapid boil down to a gentle simmer
- Cast brass burners accentuate the high-end aesthetics as well as ensuring the Power

- · Burner will withstand the extremes of mother nature
- Interconnected illuminated dials to match the suite of DCS Series 9 products

DIMENSIONS

Height	10 1/2 "	
Width	24 "	
Depth	26 7/8 "	

FFATURES & BENEFITS

Power With Control

Delivers powerful heat with exceptional control, perfect for large steam pots. Precise temperature control from 70,000 to 1,300 BTU enables a rapid boil down to a gentle simmer.

Designed To Match

With a matching look across all DCS Series 9 products, you can create a stylish, cohesive design for your Outdoor kitchen. Seamless installation and interconnectivity between products* allows for unified operation, from ignition to dial illumination.

Cooking Versatility

The grates are specially designed to provide stability for pots and woks of all sizes, eliminating the need to adjust them. Grates can also be separated into two parts to make cleaning easy.

Heavy Duty Build

Made from durable, cast brass, the burner is designed to withstand high temperatures and all types of weather.

SPECIFICATIONS

Features

2 Piece Removable Grates		•
	Cast brass burner	•
	Ignition system	Surface
	Small pot support	•
	Stainless steel cover included	•
	Wok friendly trivet	•

Finish

304 grade	Material
stainless steel	
•	Weather resistant

Gas Requirements

1/2" NPT male with 3/8" in flare adapter	•
Gas type	LPG
LP hose with regulator and Type 1 connector	•
Operational pressure	11" W.C.
Supply pressure	12" to 14" W.C.

Installation Dimensions

Cutout depth (proud)	22 3/4 "
Cutout height (proud)	10 1/8 "
Cutout width (proud)	22 1/2 "

Performance



QUICK REFERENCE GUIDE > PBE1-24-L Date: 17.12.2024 > 2

Inner ring maximum	23000 BTU	Planning Guide FR - Professional Grills Series 9 Outdoor
Minimum power	1300 BTU	- Kitchen
Outer ring maximum	47000 BTU	Planning Guide SP - Professional Grills Series 9 Outdoor Kitchen
Total Power	70000 BTU	↓ Revit-18 Power Burner
		→ Rhino-5 Power Burner
		→ Rhino-5 Power Burner with Insulated Jacket
Power Requirements		→ Rhino-5 Power Burner with Lid
		→ Rhino-5 Power Burner without Lid
Power and logic interconnectivity	•	↓ Service and Warranty
Supply frequency	60Hz	
Supply voltage	120 V	
		SketchUp-8 Power Burner without Lid
Warranty		↓ Installation Guide EN
Parts and labor	2 years	<u>↓</u> User Guide EN
		A PEACE OF MIND SALE

71467

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

Other product downloads available at dcsappliances.com

2D-DWG Power Burner

SKU

- 2D-DXF Power Burner
- Data Sheet Power Burner
- Planning Guide EN Professional Grills Series 9 Outdoor Kitchen

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com