QUICK REFERENCE GUIDE > PBE1-24-N

Date: 04.07.2024 > 1

# 24" Power Burner, Natural Gas

Series 9

Stainless Steel | Natural Gas



Easily cook for a crowd on the impressive DCS Power Burner. Designed to support different sized pots and woks, it combines powerful heat with precise temperature control from 70,000 to 1,300 BTU.

- Grates are specially designed to provide stability for pots and woks of all sizes
- Combines powerful heat with precise temperature control from 70,000 to 1,300 BTU giving you flexibility for everything from a rapid boil down to a gentle simmer

- Cast brass burners accentuate the high-end aesthetics as well as ensuring the Power Burner will withstand the extremes of mother nature
- Interconnected illuminated dials to match the suite of DCS Series 9 products

# DIMENSIONS

Height	10 1/2 "
Width	24 "
Depth	26 7/8 "

# FEATURES & BENEFITS

### Power With Control

Delivers powerful heat with exceptional control, perfect for large steam pots. Precise temperature control from 70,000 to 1,300 BTU enables a rapid boil down to a gentle simmer.

### **Designed To Match**

With a matching look across all DCS Series 9 products, you can create a stylish, cohesive design for your Outdoor kitchen. Seamless installation and interconnectivity between products\* allows for unified operation, from ignition to dial illumination.

## Cooking Versatility

The grates are specially designed to provide stability for pots and woks of all sizes, eliminating the need to adjust them. Grates can also be separated into two parts to make cleaning easy.

### **Heavy Duty Build**

Made from durable, cast brass, the burner is designed to withstand high temperatures and all types of weather.

# **SPECIFICATIONS**

#### **Features**

2 Piece Removable Grates	•
Cast brass burner	•
Ignition system	Surface
Small pot support	•
Stainless steel cover included	•
Wok friendly trivet	•

## Finish

Material	304 grade
	stainless steel
Weather resistant	•

# **Gas Requirements**

1/2" NPT male	with 3/8" in flare adapter	•
Gas type		NG
Operational p	ressure	4" W.C.
Supply pressu	re	6" to 9" W.C.

# **Installation Dimensions**

Cutout depth (proud)	22 3/4 "
Cutout height (proud)	10 1/8 "
Cutout width (proud)	22 1/2 "

# Performance



QUICK REFERENCE GUIDE > PBE1-24-N

Date: 04.07.2024 > 2

Inner ring maximum	30000 BTU	<u>↓</u> I	Rhino-5 Power Burner with Lid
Minimum power	1300 BTU	<u>↓</u> ।	Rhino-5 Power Burner without Lid
Outer ring maximum	40000 BTU	<u>↓</u> 1	Rhino-5 Power Burner
Total Power	70000 BTU	<u>↓</u> 1	Rhino-5 Power Burner with Insulated Jacket
		<u>↓</u> :	Service and Warranty
		<u>↓</u> :	SketchUp-8 Power Burner with Lid
Power Requirements		<u>↓</u> :	SketchUp-8 Power Burner without Lid
rower Requirements		<u>↓</u> :	SketchUp-8 Power Burner
Power and logic interconnectivity	•	<u>↓</u> :	SketchUp-8 Power Burner with Insulated Jacket
Supply frequency	60Hz	<u>↓</u> I	Installation Guide EN
Supply voltage	120 V	<u>↓</u> '	User Guide EN

2 years

# A PEACE OF MIND SALE

**24** Hours **7** Days a Week Customer Support T 1.888.936.7872 Wwww.dcsappliances.com

SKU 71466

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

# Other product downloads available at dcsappliances.com

↓ 2D-DWG Power Burner

Warranty

Parts and labor

- 2D-DXF Power Burner
- ↓ Data Sheet Power Burner
  - Planning Guide Professional Grills Series 9 Outdoor Kitchen
- Revit-18 Power Burner