48" Series 7 Grill, LPG

Series 7

Stainless Steel | LPG



Designed with flexibility in mind, DCS Grills allow you to cook a wide variety of meals and are engineered to deliver the functionality and power demanded by a professional chef. DCS Grills are hand-finished to perfection to complement the quality of the DCS premium outdoor kitchen and built to withstand the demands of the serious cook and the extremes of mother nature. Available in Natural and LP Gas.

• 48" Grill

DIMENSIONS

Height	24 1/4 "
Width	47 7/8 "
Depth	26 5/8 "

FFATURES & BENEFITS

Precision Heat And Control

A DCS Grill puts you in control of up to a massive 121,500 BTU per hour total power. That power lets you choose the precise heat you need from a low and slow 300° up to an intense 1100°. DCS Grills do more than help you grill an incredible steak, you can infuse smoke into your favorite meal using the built in smoker, or close the specially designed hood and use the power of convection to cook the perfect pizza. DCS Grills put you in control, giving you the versatility to cook what you want.

Double-Sided Cast Stainless Steel Grates

One side has a gentle radius for handling delicate foods. The other side is W-shaped for perfect sear lines while channeling oil away to an easily removable drip tray.

Grease Management System[™] Grease Channeling Technology

This patented technology reduces flare-ups by directing grease and oils away from the burner flames during grilling.

Smart Beam[™] Grill Light

A halogen light is designed to illuminate the entire cooking surface for perfect night grilling.

Temperature Gauge - Zero To Sear

Go from zero to sear with DCS Grills' new built-in temperature gauge. It lets you know exactly how hot the grill is, even when the hood is down.

Dedicated Sealed Smoker

Date: 24.09.2024 > 1

A dedicated smoker tray with a direct 3,500BTU burner offering a clean, convenient option for specialized smoking recipes.

SPECIFICATIONS

Accessories (sold separately)

6" accessory storage	ASH6-48
Built-in grill cover	ACBI-48
Griddle plate	BGC-GP
Hybrid IR burner	BGC-IR
Insulated jacket	BGA48-IJS (optional)
Insulated jacket (with storage accessory unit)	BGA54-IJS (optional)
On cart grill cover	ACC-48
Optional cart mount	CAD1-48

Burners

Number of U-burners

Cooking Surface Area

Primary cooking area	855 sq.in.
Total cooking area	1182 sq.in.
Warming rack area	327 sq.in.

Features

Double sided Stainless Steel grilling grates Full surface searing

QUICK REFERENCE GUIDE > BH1-48R-L

Grease management system™	•
Hood temperature gauge	•
Ignition system	Spark
Metal dials	•
Rotisserie	•
Smoker	•
Warming rack	•
Finish	
Material	304 grade stainless steel
Weather resistant	•
Gas Requirements	
1/2" NPT male with 3/8" in flare adapter	•
Gas type	

Rotisserie burner power	18000 BTU
Smoker burner power	3500 BTU
Total Power	121500 BTU
U-burner power	25000 BTU
Weight rotisserie can handle	50 lbs

Power Requirements

Grill power supply	9V Battery for Ignition
Rotisserie power supply	120V 60Hz
Product Dimensions	
Packaged weight	348 lbs
Width including rotisserie	56 3/8 "
SKU	71445

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

Other product downloads available at dcsappliances.com

- 2D-DWG Grill with 6" Storage $\overline{\mathbf{1}}$
- $\overline{\mathbf{1}}$ 2D-DXF Grill with 6" Storage
- Installation Guide Grill EN \downarrow

Guide d'installation FR $\mathbf{1}$

- $\overline{\mathbf{1}}$ Guía de instalación SP
- Service and Warranty \downarrow
- User Guide Grill EN \downarrow
- $\overline{\mathbf{1}}$ Guide d'utilisation FR
- Guía del usuario SP \downarrow

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com

1/2" NPT male with 3/8" in flare adapter	•
Gas type	LPG
LP hose with regulator and Type 1 connector	•
Operational pressure	11″ W.C.
Supply pressure	12" to 14" W.C.

Installation Dimensions

Cutout depth (proud)	22 3/4 "
Cutout height (proud)	10 1/8 "
Cutout width (proud)	45 3/4 "
Insulated jacket for proud cut-out	Varies - check manual

Performance

11125