

30" Series 9 Griddle, LPG

Series 9

Stainless Steel | LPG



Expand your outdoor kitchen options with quick cooking on the griddle. Designed with flexibility in mind, this 30" griddle can either be built-in or mounted on a freestanding cart (Grill Cart sold separately - CAD1-30E).

- Large griddle surface with precise temperature control
- Separate temperature zones and even heat distribution
- Interconnected illuminated dials to match the suite of DCS Series 9 products
- Removable slide out drip tray

DIMENSIONS

Height	10 1/2 "
Width	30 "
Depth	26 7/8 "

FEATURES & BENEFITS

Quick, Precision Cooking

Bring more cooking options to your outdoor kitchen with quick cooking on the griddle. Cook different foods at the same time with precision thermostatic control, separate temperature zones and even heat distribution.

Designed To Match

With a matching look across all DCS Series 9 products, you can create a stylish, cohesive design for your Outdoor kitchen. Seamless installation and interconnectivity between products* allows for unified operation, from ignition to dial illumination.

Safe And Convenient

Clean up is simple due to the removable slide out drip tray. For your safety, a flame failure device cuts the gas if a burner goes out.

Heavy Duty Build

Designed to withstand high temperatures and all types of weather conditions, the griddle plate is made from durable, 8mm thick 304 stainless steel.

SPECIFICATIONS

Accessories (sold separately)

Optional cart mount	CAD1-3E
---------------------	---------

Burners

Number of U-burners	2
---------------------	---

Cooking Surface Area

Total cooking area	500 sq.in.
--------------------	------------

Features

Dual temperature zones	•
Griddle plate	•
Ignition system	Surface
Stainless steel cover included	•

Finish

Available in built-in or on cart applications	•
Material	304 grade stainless steel
Weather resistant	•

Gas Requirements

1/2" NPT male with 3/8" in flare adapter	•
Gas type	LPG
LP hose with regulator and Type 1 connector	•
Operational pressure	11" W.C.
Supply pressure	12" to 14" W.C.

Installation Dimensions

Cutout depth (proud)	22 3/4 "
Cutout height (proud)	10 1/8 "
Cutout width (proud)	28 1/2 "

- ↓ 2D-DWG Griddle
- ↓ 2D-DXF Griddle
- ↓ Data Sheet Griddle
- ↓ Planning Guide EN - Professional Grills Series 9 Outdoor Kitchen
- ↓ Planning Guide FR - Professional Grills Series 9 Outdoor Kitchen
- ↓ Planning Guide SP - Professional Grills Series 9 Outdoor Kitchen
- ↓ Revit-18 Griddle
- ↓ Rhino-5 Griddle with Lid
- ↓ Rhino-5 Griddle without Lid
- ↓ Rhino-5 Griddle
- ↓ Rhino-5 Griddle with Insulated Jacket
- ↓ Service and Warranty
- ↓ SketchUp-8 Griddle with Lid
- ↓ SketchUp-8 Griddle without Lid
- ↓ SketchUp-8 Griddle
- ↓ SketchUp-8 Griddle with Insulated Jacket
- ↓ User Guide FR
- ↓ Installation Guide EN
- ↓ User Guide EN

Performance

Total Power	40000 BTU
U-burner power	20000 BTU

Power Requirements

Power and logic interconnectivity	•
Supply frequency	60Hz
Supply voltage	120 V

Warranty

Parts and labor	2 years
-----------------	----------------

SKU	71465
-----	-------

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 W www.dcsappliances.com

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

Other product downloads available at dcsappliances.com